



PoolSync  
**READY!**



Engineered to  
**HEAT & COOL**  
in diverse climates

Control from a  
**CONVENIENT**  
phone app



**TropiCal®**

# KEEP YOUR POOL AT PERFECT TEMPERATURE ALL SEASON LONG

- ICEBREAKER® heat and cool - extends swimming season longer than any other heat pump on the market
- Continues to heat at freezing temperatures to minimize heat loss
- Cools your pool to a refreshing temperature
- Patented high performance ThermoLink® titanium heat exchanger maximizes flow efficiency
- Weather protected microprocessor control with full text LCD display is easy to use and compatible with most external controllers
- Impact resistant, rust and fade proof cabinet with built-in drain pan provides condensate management
- Quieter than conventional heat pumps

## Now PoolSync® Ready

- Adjust your temperature setting right through your phone in the PoolSync app

\*Additional purchase of PoolSync WiFi Controller required



<b>T135R</b>		
<b>BTUs</b> <small>(water temp/ambient air/ relative humidity)</small>	80/80/80	123,000
	80/80/63	118,000
	80/50/63	78,000
<b>C.O.P.</b> <b>Coefficient of Performance</b> <small>(water temp/ambient air/ relative humidity)</small>	80/80/80	5.5
	80/80/63	5.2
	80/50/63	4.0
<b>Refrigerant</b>		R410A
<b>Heat Exchanger</b>		ThermoLink®
<b>Electrical</b>	kW Input	6.7
	Voltage/Hz/Phase	208-230/60/1
	Min. Circuit Ampacity	43.3
	Max. Fuse Size	60
<b>Water Flow</b>	Min./Max. (gpm)	30/70
A Heater Bypass Kit is required when flow rates exceed the maximum: part number STK0135.		
<b>Physical</b>	Weight (lbs)	264
	Length x Width x Height (in)	34" x 34" x 39"
<b>Shipping</b>	Weight (lbs)	304
	Length x Width x Height (in)	37" x 36" x 45"

Rated in accordance with AHRI standard 1160 water temp/ambient air/relative humidity  
Specifications subject to change



**A portion of every heat pump sold will be donated to Every Child a Swimmer**



**WWW.AQUACAL.COM**

MADE IN USA 



California residents visit [aquacal.com](http://aquacal.com) for Proposition 65 information.



AC-2408 03\_24\_V2