

TropiCal®

TEAM HORNER Employee Owned

GET THE MOST OUT OF YOUR POOL HEATING INVESTMENT!

- High performance titanium heat exchanger maximizes flow efficiency (Patented ThermoLink® in T115 and T135)
- Weather protected microprocessor control with full text LCD display is easy to use and compatible with most external controllers
- Impact resistant, rust and fade proof cabinet with built-in drain pan provides condensate management
- Quieter than conventional heat pumps

Now PoolSync® Ready Pa

 Adjust the mode to heat, cool or autotemp, and set your temperature through the PoolSync app





		T75R	T115R	T135R
Efficiency	kW Output	17.9	25.2	32.2
	BTU Output	61,000	86,000	110,000
	C.O.P. Coefficient of Performance	6.4	6.6	7.2
	kW Input	2.8	3.8	4.5
Electrical	Heat or Heat & Cool	H & C	H & C	H & C
	Voltage/Hz/Phase	H & D	H & D	D
H - 200-240/50/1 D - 380-420/50/3	Max. Fuse Size	H - 35 D - 15	H - 60 D - 25	D - 25
	Min. Circuit Ampacity	H - 24.7 D - 8.8	H - 38.6 D - 15.2	D - 17.2
Refrigerant		R410A	R410A	R410A
Heat Exchanger		Tube in Tube	ThermoLink® III	ThermoLink® III
Water Flow	Min./Max. (m³/h)	4.5/10.2	6.8/15.9	6.8/15.9
	Min./Max. (gpm)	20/45	30/70	30/70
	A Heater Bypass Kit is required when flow rates exceed the maximum: part number STK0135			
Physical	Weight (kg)	96	121	122
	Weight (lbs)	210	265	267
	Length x Width x Height (cm)	87 x 87 x 72	87 x 87 x 100	87 x 87 x 100
	Length x Width x Height (in)	34" x 34" x 28"	34" x 34" x 39"	34" x 34" x 39"
Shipping	Weight (kg)	114	139	140
	Weight (lbs)	250	305	307
	Length x Width x Height (cm)	94 x 92 x 87	94 x 92 x 115	94 x 92 x 115
	Length x Width x Height (in)	37" x 36" x 34"	37" x 36" x 45"	37" x 36" x 45"
	Specifications subject to change			

Specifications subject to change



A portion of every heat pump sold will be donated to Every Child a Swimmer











